


<b>Model NO.</b>	<b>SUC-H123</b>
	
<b>Sensor</b>	·1/3-inch CMOS/ CCD optional
<b>Support Protocol</b>	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, Ipsec, UPnP, RTP, and RTCP
<b>Embedded Processor (HISILION Hi 3512)</b>	<ul style="list-style-type: none"> <li>· ARM926EJ-S, 32-bit RISC processor, Harvard architecture</li> <li>· 16 KB instruction cache and 16 KB data cache</li> <li>· 2 KB tight coupled instruction memory</li> <li>· Built-in MMU for open OS</li> <li>· Up to 264 MHz</li> </ul>
<b>Video Codec</b>	<ul style="list-style-type: none"> <li>· H.264 Main Profile@Level3.0 encoding and decoding</li> <li>· H.264 Baseline Profile@Level3.0 encoding and decoding</li> <li>· MJPEG/JPEG Baseline encoding and decoding</li> </ul>
<b>Video Codec Performance</b>	· Dual stream encoding (H.264/MJPEG)
<b>Resolution</b>	D1 720*576 Half D1 720*288 CIF 320*288
<b>Frame Rate</b>	PAL: 1-25 fps NTSC: 1-30 fps
<b>Audio</b>	G.726 compression
<b>POE</b>	support IEEE 802.3af
<b>Lens</b>	4mm/6mm fixed lens optional
<b>Waterproof Level</b>	IP 66
<b>IR LED distance</b>	60 PCS of IR LED/30 m
<b>Client Software</b>	Support Multi-Screen software and CMS
<b>Alarm</b>	·1 Channel output
<b>Power Supply</b>	·12V DC ,1A
<b>Working Temperature</b>	·-10 to +55°C
<b>Working Humidity</b>	·10 to 85%