

Product	Pan/Tilt IR IP Dome Camera
Model NO.	SUD-H231
	
Support Protocol	TCP,UDP,IP,HTTP,FTP,SMTP,DHCP,DNS,ARPCMP,POP3,NTP,RTP, and RTCP
Embedded Processor (HISILION Hi 3512)	<ul style="list-style-type: none"> ARM926EJ-S, 32-bit RISC processor, Harvard architecture · 16 KB instruction cache and 16 KB data cache · 2 KB tight coupled instruction memory · Built-in MMU for open OS · Up to 264 MHz
Video Codec	<ul style="list-style-type: none"> · H.264 Main Profile@Level3.0 encoding and decoding · H.264 Baseline Profile@Level3.0 encoding and decoding · MJPEG/JPEG Baseline encoding and decoding
Video Codec Performance	· Dual stream encoding (H.264/MJPEG)
Resolution	D1 720*576 Half D1 720*288 CIF 320*288
Frame Rate	PAL: 1-25 fps NTSC: 1-30 fps
Horizontal rotation range	0° -355 °
Vertical rotation range	0° -90°
Rotation speed	Horizontal0.1-300°/S Vertical: 45°/S
Number of preset	128
RS-485 Protocols	Pelco-D/ Pelco-P
Audio	G.726 compression
Two way Audio	support Two way audio
POE	support IEEE 802.3af
Client Software	support Multi-Screen software and CMS
Alarm	1 Channel output
Lens	4/6 mm fixed Lens
Power Supply	12V DC ,1A
Power consumption	<5W
Working Temperature	-10 to +55°C
Working Humidity	10 to 85%